

10.00


PCB Terminal Block

- 10.00 mm Pin Spacing
- Board Mount PCB
- 16A Current Rating
- Height 16.3mm
- Modular



MI25xx-10-IQ

45° Angled Wire Entry



Electrical Ratings		UL E178356		IEC	VDE N.40019705
Usergroup	B	C	D	-	
Rated Voltage	300V	-	300V	750V	
Rated Current	16A	-	16A	16A	
Wire Size	<i>solid</i>	30-14 AWG	-	30-14 AWG	0.25mm ² - 4.0mm ²
	<i>stranded</i>	30-14 AWG	-	30-14 AWG	0.25mm ² - 2.5mm ²

Ordering Information

No. Poles	Length (mm)	Std. Pack	Order #
2	15	100	MI252-10-IQ
3	25	100	MI253-10-IQ
4	35	100	MI254-10-IQ
5	45	100	MI255-10-IQ
6	55	100	MI256-10-IQ

Material Specifications	
Clamp	Nickeled Copper
Solder tab	Tin-Plated Copper
Screw	Galvanized Steel
Insulating Material	Polyamide
Flammability Class	V0 UL94
Operating Temperature	-30°C - +105°C

Installation Data	
Screw Size	M3
Torque	0.5 Nm (4.5 lb.in.)
Stripping Length	max. 8mm
Clamp Opening	2.8 x 2.8mm
PCB Hole Size	1.3mm

