

PCB Terminal Block


10.00 mm Pin Spacing

- Board Mount PCB
- 24A Current Rating
- Height 12.5mm
- Modular



MIP25xx-10-IQ

45° Angled Wire Entry



Screw
Cage Clamp
(lift type)

Electrical Ratings

					
Usergroup	B	C	D	-	
Rated Voltage	300V	-	300V	750V	
Rated Current	24A	-	24A	24A	
Wire Size	<i>solid</i>	30-12 AWG	-	30-12 AWG	0.25mm ² - 4.0mm ²
	<i>stranded</i>	30-12 AWG	-	30-12 AWG	0.25mm ² - 2.5mm ²

Ordering Information

No. Poles	Length (mm)	Std. Pack	Order #
2	15	100	MIP252-10-IQ
3	25	100	MIP253-10-IQ
4	35	100	MIP254-10-IQ
5	45	100	MIP255-10-IQ
6	55	100	MIP256-10-IQ


Material Specifications

Clamp	Nickel Copper
Solder tab	Tin-Plated Copper
Screw	Galvanized Steel
Insulating Material	Polyamide
Flammability Class	V0 UL94
Operating Temperature	-30°C - +105°C

Installation Data

Screw Size	M3 
Torque	0.5Nm (4.5 lb.in.)
Stripping Length	max. 8mm
Clamp Opening	2.8 x 2.8mm
PCB Hole Size	1.5mm

Dimensions (mm)



Drilling Diagram

