


PCB Terminal Block

- 10.00 mm Pin Spacing
- Board Mount PCB
 - 20A Current Rating
 - Height 29.5mm
 - Modular
 - High Profile



MMT25xx-10-V

Front Wire Entry, High Profile



Electrical Ratings			 E178356		  N.40019705
Usergroup		B	C	D	-
Rated Voltage		300V	-	300V	750V
Rated Current		20A	-	20A	20A
Wire Size	<i>solid</i>	30-12 AWG	-	30-12 AWG	0.25mm² - 4.0mm²
	<i>stranded</i>	30-12 AWG	-	30-12 AWG	0.25mm² - 2.5mm²

Ordering Information

No. Poles	Length (mm)	Std. Pack	Order #
2	15	100	MMT252-10-V
3	25	100	MMT253-10-V
4	35	100	MMT254-10-V
5	45	100	MMT255-10-V
6	55	100	MMT256-10-V
7	65	100	MMT257-10-V
8	75	100	MMT258-10-V

Material Specifications	
Clamp	Nickel-Copper
Solder tab	Tin-Plated Copper
Screw	Galvanized Steel
Insulating Material	Polyamide
Flammability Class	V0 UL94
Operating Temperature	-30°C - +105°C

Installation Data	
Screw Size	M3
Torque	0.5Nm (4.5 lb.in.)
Stripping Length	max. 7.5mm
Clamp Opening	2.8 x 2.8mm
PCB Hole Size	1.3mm

