

5.00


PCB Terminal Block

5.00 mm Pin Spacing

- Board Mount PCB
- 20A Current Rating
- Height 29.5mm
- Modular
- High Profile

**MMT25xx-5-V**

Front Wire Entry, High Profile

**Electrical Ratings**

Usergroup	B	C	D	-
Rated Voltage	300V	-	300V	450V
Rated Current	20A	-	20A	20A
Wire Size	<i>solid</i> 30-12 AWG	-	30-12 AWG	0.25mm ² - 4.0mm ²
	<i>stranded</i> 30-12 AWG	-	30-12 AWG	0.25mm ² - 2.5mm ²

Ordering Information


No. Poles	Length (mm)	Std. Pack	Order #
2	10	100	MMT252-5,00-V
3	15	100	MMT253-5,00-V
4	20	100	MMT254-5,00-V
5	25	100	MMT255-5,00-V
6	30	100	MMT256-5,00-V
7	35	100	MMT257-5,00-V
8	40	100	MMT258-5,00-V
9	45	100	MMT259-5,00-V
10	50	100	MMT2510-5,00-V
11	55	100	MMT2511-5,00-V
12	60	100	MMT2512-5,00-V

Material Specifications

Clamp	Nickel-Copper
Solder tab	Tin-Plated Copper
Screw	Galvanized Steel
Insulating Material	Polyamide
Flammability Class	V0 UL94
Operating Temperature	-30°C - +105°C

Installation Data

Screw Size	M3
Torque	0.5Nm (4.5 lb.in.)
Stripping Length	max. 7.5mm
Clamp Opening	2.8 x 2.8mm
PCB Hole Size	1.3mm

Dimensions (mm)**Drilling Diagram**