


PCB Terminal Block

- 10.00 mm Pin Spacing
- Board Mount PCB
 - 26A Current Rating
 - Height 12.8mm
 - Single Mold Terminal



MVE26xx-10-V

Front Wire Entry



Box Clamp with Wire Protector

Electrical Ratings

		C ^{UL} US E178356			IEC	VDE N.40019705
Usergroup		B	C	D		-
Rated Voltage		300V	600V	600V		1000V
Rated Current		26A	-	26A		24A
Wire Size	<i>solid</i>	30-12 AWG	-	30-12 AWG		0.25mm ² - 4.0mm ²
	<i>stranded</i>	30-12 AWG	-	30-12 AWG		0.25mm ² - 2.5mm ²

Ordering Information

No. Poles	Length (mm)	Std. Pack	Order #
2	15	200	MVE262-10-V
3	25	200	MVE263-10-V
4	35	100	MVE264-10-V
5	45	100	MVE265-10-V
6	55	100	MVE266-10-V


Material Specifications

Clamp	Tin-Plated Copper
Solder tab	Tin-Plated Copper
Screw	Galvanized Steel
Insulating Material	Polyamide
Flammability Class	V0 UL94
Operating Temperature	-30°C - +105°C

Installation Data

Screw Size	M3
Torque	0.5Nm (4.5 lb.in.)
Stripping Length	max. 7.5mm
Clamp Opening	3.0 x 2.5mm
PCB Hole Size	1.5mm

Dimensions (mm)



Drilling Diagram

