


PCB Terminal Block

- 5.08 mm Pin Spacing
- Board Mount PCB
 - 20A Current Rating
 - Height 13.5mm
 - Modular



MVES15xx-5,08-V

Front Wire Entry



Electrical Ratings		UL E178356		IEC	VDE N.40019705
Usergroup	B	C	D		-
Rated Voltage	300V	-	300V		250V
Rated Current	20A	-	20A		24A
Wire Size	<i>solid</i>	30-14 AWG	-	30-14 AWG	0.25mm ² - 2.5mm ²
	<i>stranded</i>	30-14 AWG	-	30-14 AWG	0.25mm ² - 2.5mm ²

Ordering Information

No. Poles	Length (mm)	Std. Pack	Order #
2	10.16	200	MVES152-5,08-V
3	15.24	200	MVES153-5,08-V
4	20.32	100	MVES154-5,08-V
5	25.40	100	MVES155-5,08-V
6	30.48	100	MVES156-5,08-V
7	35.56	100	MVES157-5,08-V
8	40.64	100	MVES158-5,08-V
9	45.72	100	MVES159-5,08-V
10	50.80	100	MVES1510-5,08-V
11	55.88	100	MVES1511-5,08-V
12	60.96	100	MVES1512-5,08-V
13	66.04	50	MVES1513-5,08-V
14	71.12	50	MVES1514-5,08-V
15	76.20	50	MVES1515-5,08-V
16	81.28	50	MVES1516-5,08-V
17	86.36	50	MVES1517-5,08-V
18	91.44	50	MVES1518-5,08-V
19	96.52	50	MVES1519-5,08-V
20	101.60	50	MVES1520-5,08-V
21	106.68	50	MVES1521-5,08-V
22	111.76	50	MVES1522-5,08-V
23	116.84	50	MVES1523-5,08-V
24	121.92	50	MVES1524-5,08-V

Material Specifications	
Clamp	Tin-Plated Copper
Solder tab	Tin-Plated Copper
Screw	Galvanized Steel
Insulating Material	Polyamide
Flammability Class	V0 UL94
Operating Temperature	-30°C - +105°C

Installation Data	
Screw Size	M2.5
Torque	0.4 Nm (3.6 lb.in.)
Stripping Length	max. 7mm
Clamp Opening	2.6 x 2.6mm
PCB Hole Size	1.5mm

