

PCB Terminal Block

- 7.62 mm Pin Spacing
- Board Mount PCB
 - 20A Current Rating
 - Height 19mm
 - Modular



MVSP27xx-7,62-V

Front Wire Entry



Screw
Cage Clamp
(lift type)

Electrical Ratings		UL E178356		IEC	VDE N.40019705
Usergroup	B	C	D	-	
Rated Voltage	300V	-	300V	750V	
Rated Current	20A	-	20A	24A	
Wire Size	<i>solid</i>	30-14 AWG	-	30-14 AWG	0.25mm ² - 4.0mm ²
	<i>stranded</i>	30-14 AWG	-	30-14 AWG	0.25mm ² - 2.5mm ²

Ordering Information

No. Poles	Length (mm)	Std. Pack	Order # - Modular
2	15.24	100	MVSP-272
3	22.86	100	MVSP-273
4	30.48	100	MVSP-274
5	38.10	100	MVSP-275
6	45.72	100	MVSP-276
7	53.34	100	MVSP-277
8	60.96	100	MVSP-278
9	68.58	100	MVSP-279
10	76.20	100	MVSP-2710
11	83.82	100	MVSP-2711
12	91.44	100	MVSP-2712

Material Specifications	
Clamp	Tin-Plated Copper
Solder tab	Tin-Plated Copper
Screw	Galvanized Steel
Insulating Material	Polyamide
Flammability Class	V0 UL94
Operating Temperature	-30°C - +105°C

Installation Data	
Screw Size	M3
Torque	0.8 Nm (4.5 lb.in.)
Stripping Length	max. 9.5mm
Clamp Opening	2.8 x 4mm
PCB Hole Size	1.5mm

