


PCB Terminal Block

- 10.16 mm Pin Spacing
- Board Mount PCB
 - 16A Current Rating
 - Height 43.0mm
 - Modular
 - 3-Level



MVT25xx-10,16-V

Front Wire Entry / 3-Level



Screw
Cage Clamp
(lift type)

Electrical Ratings		UL E178356		IEC	VDE N.40019705
Usergroup	B	C	D	-	
Rated Voltage	300V	-	300V	750V	
Rated Current	16A	-	16A	16A	
Wire Size	<i>solid</i>	30-14 AWG	-	30-14 AWG	0.25mm ² - 4.0mm ²
	<i>stranded</i>	30-14 AWG	-	30-14 AWG	0.25mm ² - 2.5mm ²

Ordering Information

No. Poles	Length (mm)	Std. Pack	Order #
6	15.24	100	MVTB-252
9	25.40	100	MVTB-253
12	35.56	100	MVTB-254
15	45.72	100	MVTB-255
18	55.88	100	MVTB-256
21	66.04	100	MVTB-257
24	76.20	100	MVTB-258
27	86.36	100	MVTB-259
30	96.52	100	MVTB-2510
33	106.68	100	MVTB-2511
36	116.84	100	MVTB-2512

Material Specifications	
Clamp	Nickel Copper
Solder tab	Tin-Plated Copper
Screw	Galvanized Steel
Insulating Material	Polyamide
Flammability Class	V0 UL94
Operating Temperature	-30°C - +105°C

Installation Data	
Screw Size	M3
Torque	0.5Nm (4.5 lb.in.)
Stripping Length	max. 8mm
Clamp Opening	2.8 x 2.8mm
PCB Hole Size	1.3mm

